

## Graffgo/Flygo Data Sheet

Reference	Graffgo Anti-Graffiti Coating
Purpose	A one pack single coat permanent non-sacrificial coating giving excellent protection against fly poster and graffiti attack. The product allows easy repeated removal of graffiti by using water/detergent
Colour	Clear and Pigmented Liquid
Application	Apply by brush, roller, convention or airless spray.
Volume Solids	78% Matt; 78% Gloss; 48% Pigmented
Recommended Film Thickness	DFT to be determined by Urban Hygiene LTD depending on substrate and porosity, normally between 50 to 80 DFT
Coverage Rate	Theoretical 8 to 10 square metres/litre
Drying Time	Touch dry 3 / 4 hours; full cure 24 hours. Recoating (if required) time 3 to 4 hours
Thinners/Brushwash	Disposal
Weight Per Litre	.90-1.02
Flash Point	Above 64deg C.
V.O.C	50 grams per litre
Finish	Gloss – Semi Matt
Application Temperature	-5DegC +60DegC
Surface Preparation	All surfaces must be clean and dry, remove any soiling by power wash etc. Any soiling/graffiti apparent on painted surfaces i.e. masonry /rendered walls should be re-painted with good quality masonry exterior paint, prior to application. Non-Darkening Primer should be applied prior to top coat on all sandstone/brick surfaces

Issue Date: 05.02.2018