

## Urban "easy-on" Anti Mould Varnish

### Description

Keep damp ceilings and walls completely mould free for up to 20 years with easy-on Anti-Mould Wall and Ceiling Varnish. Applied by brush, roller or spray, one coat cures to form a mould repelling, fungus fighting, super durable barrier that can be wiped clean 1000's of times if necessary and won't support black mould or fungal degradation. easy-on Anti-Mould Wall and Ceiling Varnish is hydrophobic, lipophobic and antimicrobial therefore reducing or completely eliminating water and pink or orange (bacteria) staining on shower or bathroom walls. Apply easy-on Anti-Mould Wall and Ceiling Varnish over clean and dry, tiled or painted surfaces and ceilings to vastly extend redecoration intervals, improve appearances and advance hygiene.

### **Advantages**

- Anti-mould paint varnish protection
- Super tough cleans 1000's of times
- Single coat, high gloss paint sealer
- Hydrophobic bathroom wall paint
- Lipophobic wall and tile varnish
- Oleophobic protection for surfaces
- Self-cleaning tile and grout varnish
- Prevents black mould on ceilings
- Up to 20-year mould fighting life
- Scrubbable bathroom wall finish
- Suited for high humidity areas
- Damp/moisture tolerant once cured
- Non-yellowing clear gloss finish
- Washable protective coating
- Antimicrobial silver ion system
- Fully breathable wall protection

### Simple application instructions:

Coating performance is proportional to the degree of surface preparation. Surfaces must be clean, dry (<6% moisture), undamaged and free of all contaminants prior to coating.

- 1) Add total contents of Cure tin into Resin tin and stir or re-lid and shake until mixed.
- 2) Apply one thin coat by brush, roller or spray without diluting.
- 3) If bubbles are created, flow these out with a dry brush for an optimum flat finish.
- 4) Leave to dry for 4 hours @20C and protect from dust, dirt, rain, etc.

On porous surfaces 2 coats may be necessary.

## Technical Data & Physical Data

**Colour:** Transparent

**Finish:** Gloss Sheen

**Mix Ratio:** 5 : 1 Resin/Cure

**Substrates:** Concrete, tile, mortar, existing coatings, metals, timber.

**Components:** 2 (resin + cure)

**Curing mechanism:** Chemical reaction between components

**Dry film thickness:** 25 - 50 microns

**Number of coats:** 1 (usually)

**Moisture permeability:** 35gm/ m<sup>2</sup>/24 hours

**SG of mixed product:** 1.10 kg/L

**VOC content:** <8% weight

**Calculated coverage:** 33 m<sup>2</sup> per litre @ 25 microns

**Practical coverage:** 9-33 m<sup>2</sup> per litre dependent upon surface, porosity and texture.

**Application:** By brush, roller, low pressure HVLP or conventional spray equipment.