

## Urban “easy-does it” Invisible Wooden Decking Sealer

### Description

Protect and revive wooden surfaces for up to 10 years with Urban’s – “easy-does-it” Invisible Wooden Decking Sealer, perfect for decking, fencing, wooden panelling and worktops inside and out. This super durable long-life impregnation coating penetrates deep into wood such as oak, spruce, pine, Douglas fir, (and even pressure-treated wood) to upgrade its durability and give an unparalleled level of protection from weathering, spills, UV and dirt. Invisible Wooden Decking Sealer will reduce the maintenance your wooden surfaces require whilst simultaneously extending their lifespan. Solvent-free protection for all of your oak, pine, Douglas fir and spruce wooden fences, decking and surfaces.

### Advantages

- Suppresses residual damp/moisture
- Clear, invisible protection for wood
- Greatly enhances durability
- Hydrophobic water repelling
- Resists oil, petrol and grease
- Decreases the aging of wood
- Solvent free-Environmentally friendly
- Resistant to dirt, UV and pollution
- Freeze – thaw stable (breathable)
- Resistant to rain and weathering
- Prevents moss and algae build-up
- Reduces annual maintenance required
- Fantastic 10 year expected performance
- For wood decking, fencing and paneling

### Uses

For use internally and externally to all bare woods where protection is desired, such as oak, pine, spruce, Douglas fir, pressure-treated wood etc.

- Decking
- Fencing
- Weatherboarding
- Panelling
- Garden furniture
- Joinery - kitchen worktops etc.

### Application

2 coat application by means of low-pressure spray, brush or roller

Equipment Care:

All equipment should be cleaned with water immediately after use.

### Colour

Clear / Invisible

## **Coverage Rate**

3-5 m<sup>2</sup>/Litre depending on substrate type

\*Please note – Urban Hygiene recommend a small trial area to ensure correct application levels are used to obtain the required performance properties subjected to the differing porosity levels of porous wooden materials.

## **Preparations:**

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Urban Soft Wash Algae Remover.

- New wood and in general - the surface must be sound, clean, dry, free from frost, laitance, oil, grease and all dust, loose and friable materials must be completely removed from surfaces before application
- Resinous or greyed wood: clean and rinse thoroughly, clean off all dust and dry the wood.
- Damaged wood: sand down to bare wood, clean off all dust and dry the wood. It is recommended to vacuum all residual dust left from sanding process.

## **Limitations of Use**

The treatment may be ineffective in the following cases:

- On varnished, waxed, heat treated, polished, highly brushed, rectified, modified or THT (high-temperature treatment) woods.
- On damp wood (moisture content > 16%).
- Where micro-organisms or insects are present (pre-treatment necessary).
- Poor application, preparation and quality of substrate type
- On sapwood.
- Untested application on exotic or resinous wood.
- On wood that has undergone a fire-resistance treatment.
- On sharp edges (sharp edges should preferably be rounded to ensure continuity of product and thus avoid breaks in coverage).
- On floors.
- Ends, cuts, drill holes, etc. not saturated with product.

## **Storage**

Storage is in a cool, dry place with temperatures between 10-15°C. Do not allow to freeze.

## **Shelf Life:**

12 months (in original sealed container).