

Urban "easy-does-it" Back To Black Tarmac Restorer

Description

Bring tired old driveways, pavements, car parks and playgrounds back to life with Urban's easy-does-it Back To Black Tarmac Rejuvenator. Available in Red or Black, one coat of this solvent-free, decorative protection coating is all you will need to breathe new life into old tired tarmac sealed surfaces. With a super durable 10 year expected life and full oil, petrol, soiling and UV resistance Back To Black Tarmac Rejuvenator is the best way to improve the appearance of your tarmac floors. Ideal for Car parks, Playgrounds, Pathways and Drives.

Advantages

- Avoids expensive resurfacing
- Enhances durability - extended life of surface
- Excellent water repellence
- Excellent resistance to oil penetration.
- Excellent Stain Resistance
- Resistant to Dirt and Pollution
- Resistant to Weathering & delays aging
- Prevents weed growth moss and algae forming
- Permeable to Water Vapour (breathable)
- Flexible
- UV, Chemical & abrasion resistant
- Reduces maintenance required
- Prevents cracks
- Upgrades "dull" existing surfaces
- Environmentally friendly
- Up to 10 years product performance

Uses

For use externally upon domestic, commercial or industrial areas including:

- Driveways
- Footpaths
- Pavements
- Car Parks

Colour Range:

Black and Red

Pack Size:

Supplied in 5 litre jerry cans.

Coverage Rate:

This is dependent upon the surface porosity. Average coverage in the region of 2-4m² per litre.

Drying Time:

Touch dry - 4 hours @ 20°C

Hard dry - 24 hours @ 20°C

Preparation:

Ensure surfaces to be treated are clean, dry, free from frost, laitance, oil, grease and all dust, loose and friable materials must be completely removed before application of Urban "easy-does-it" Back to Black Tarmac Restorer.

- Mould, fungi and organic growth present
- General grime on substrate
- Oil / grease present
- Cement, Grout and mortar spillages

Application:

One coat by brush, roller or spray. A second coat maybe required on very porous substrates.

Equipment Care:

All equipment should be cleaned immediately with water after use.

Storage:

Recommended storage is in a cool, dry place with temperatures between 10-15°C.

Do not allow to freeze.

Shelf Life:

12 months (in original sealed container).

Health & Safety:

Refer to MSDS

Data provided on this TDS is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred, and customers are advised to carry out their own tests under local conditions.