

## Urban "easy-on" Anti Graffiti Coating

### Description

easy-on permanent anti-graffiti coating is our #1 transparent, graffiti resistant finish for all internal and external walls, bridges, subways, murals and street art. Applied by brush, roller or spray, one coat easy-on anti-graffiti clear glaze cures to a graffiti resistant finish in 4 hours and easily withstands hundreds of graffiti removal operations over its proven 20-year life. easy-on anti-graffiti coating is effective against all types of graffiti media including permanent marker pen, spray paint and fly-poster attacks, so whether you're looking to protect the latest Banksy, defend a subway, bridge or shopping centre from unwanted graffiti vandalism or keep your train, bus or street signs looking pristine, easy-on permanent anti-graffiti coating is the clear graffiti resistant varnish for you.

### **Advantages**

- Clear Gloss Anti-graffiti coating
- Easily applied to any surface
- Incredible 20+ year permanent life
- easy-on withstands 100's of cleans
- Class 0 Fire Rated graffiti protection
- Best value wall cladding alternative
- Permanent anti-graffiti coating
- Single coat wall protection coating
- Saves painted and unpainted walls
- Resists all permanent marker pens
- Repels graffiti spray paint tagging
- Safe with easy-off graffiti remover
- Permanent anti-graffiti resistance
- Solvent-free, Low VOC and Odour

### Simple application instructions:

Coating performance is proportional to the degree of surface preparation. Surfaces must be clean, dry (<6% moisture), undamaged and free of all contaminants prior to coating.

- 1) Add total contents of Cure tin into Resin tin and stir or re-lid and shake until mixed.
- 2) Apply one thin coat by brush, roller or spray without diluting.
- 3) If bubbles are created, flow these out with a dry brush for an optimum flat finish.
- 4) Leave to dry for 4 hours @20C and protect from dust, dirt, rain, etc.

On porous surfaces 2 coats may be necessary.

## Technical Data & Physical Data

**Colour:** Transparent

**Finish:** Gloss Sheen

**Mix Ratio:** 5 : 1 Resin/Cure

**Substrates:** Concrete, tile, mortar, existing coatings, metals, timber. **Components:** 2 (resin + cure)

**Curing mechanism:** Chemical reaction between components

**Dry film thickness:** 25 - 50 microns

**Number of coats:** 1 (usually)

**Moisture permeability:** 35gm/ m<sup>2</sup>/24 hours

**SG of mixed product:** 1.10 kg/L

**VOC content:** <8% weight

**Calculated coverage:** 33 m<sup>2</sup> per litre @ 25 microns

**Practical coverage:** 9-33 m<sup>2</sup> per litre dependent upon surface, porosity and texture.

**Application:** By brush, roller, low pressure HVLP or conventional spray equipment.

